## U.S. Department of Labor

Mine Safety and Health Administration Approval and Certification Center 765 Technology Drive Triadelphia, West Virginia 26059



In Reply Refer To: MSHA:A&CC:PAR 98158 Record File No.IC-152/16

August 12, 2010

Ms. Patrizia Di Deo Alfagomma SpA Nucleo Industriale 64020 S. Atto (Teramo) ITALY

Dear Ms. Di Deo:

The review of your application dated March 31, 2010, Company Code No. 130610, for the "1306" hydraulic hose cover compound is complete.

This construction and the information provided meet the requirements of the <u>Standard Application Procedures for Acceptance of Flame-Resistant Solid Products Taken into Mines.</u>

The following requirements apply to this acceptance:

- 1. Acceptance Marking No. "MSHA IC-152/16" must be permanently marked on the product with letters at least 1/4" high and at intervals not exceeding 3 feet. Other types of permanent markings may be used with prior approval of MSHA.
- 2. The accepted range of material thickness is 0.9 mm to 1.4 mm.
- 3. You are obligated as the manufacturer to maintain the quality of the product to assure the requirements of this acceptance are being met.
- 4. Any change in product composition or in any other factors that may affect this acceptance must not be made without prior authorization from MSHA.
- 5. We have the right to revoke this acceptance for cause at any time.
- 6. We must be notified of any transfer of production or ownership of this product.

An invoice for the cost of processing this action will be forthcoming.

If you have any comments or questions relative to this letter, please refer them to David Creamer at 304-547-0400.

Sincerely,

Kenneth A. Sproul

Acting Chief, Approval and Certification Center

Dewid C. almin for