



BREWERY HOSE



// BREWERY S&D HOSE-EXTRA FLEXIBLE

MAIN FEATURES:

- ▲ HIGH TEMPERATURE CONSTANT 108 °C (226 °F)
- ▲ EXTRA FLEXIBLE
- ▲ WHITE CHLOROBUTYL TUBE, MEETS FDA AND 3A REQUIREMENTS

APPLICATIONS:

- // Micro-brewery and brewery suction & discharge
- // Liquid food and alcoholic beverage suction & delivery
- // Specially designed for wine, beer and spirits, up to 95 proof
- // Versatile hose for brewery applications requiring superb flexibility and lightweight characteristics



// 422LH



Alcoholic beverages S&D 10 bar (150 psi)

Tube: white chlorobutyl.

Reinforcement: high tensile textile cords with embedded helix wires.

Cover: red NR/EPDM – abrasion and ozone resistant.

Application: liquid food and alcoholic beverages suction and delivery max 95% proof.

Sterilize with 130 °C (266 °F) steam for 30 minutes or with 5% soda solution.

Constant operation: -30 °C +108 °C (-22 °F +226 °F)

↔		↔		↻		↻		⤴		⚠		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
25,0	1"	35,0	1.38	10	150	30	450	51,0	2	100	0,70	0.47	
32,0	1 1/4"	42,0	1.65	10	150	30	450	63,0	2 1/2	100	0,86	0.58	
38,0	1 1/2"	48,0	1.89	10	150	30	450	76,0	3	100	1,00	0.67	
51,0	2"	61,0	2.40	10	150	30	450	102,0	4	100	1,31	0.88	
63,0	2 1/2"	76,0	2.99	10	150	30	450	127,0	5	100	2,37	1.59	
76,0	3"	90,0	3.54	10	150	30	450	152,0	6	90	3,03	2.04	
102,0	4"	116,0	4.57	10	150	30	450	204,0	8	90	3,98	2.67	